



Applications

- Sport Lighting
- Stadium Lighting
- Large area Lighting
- High Mast Lighting
- Construction Sites
- Coal yards
- Airport Aprons
- Security Lighting

Features

- High Lumen output
- Compact Linear Lamp for Excellent optical control
- Cooler base design for improved field operation
- Low Current Consumption

Description	Base	Part Code	Initial Lumens	Avg. Life Hours	Colour Temp.	CRI	LPW	Burn Position	Operating Current (A)	Carton Qty.	Control Gear
MBIL S 1000 W	Rx7s	22417	80000	6000	5200	65	80	Hor ± 15*	4.40	6	MH
MBIL S 1500 W	Rx7s	22151	130000	6000	5200	65	87	Hor ± 15*	6.70	6	MH
MBIL S 2000 W	Rx7s	22132	215000	6000	5200	65	100	Hor ± 15*	10.30	2	MH
MH-TS 2000 W/L/K 12/45K	Cable/Lug	84203	240000	5000	4500	65	112	Hor ± 15*	10.30	1	MH
MH-TS 2000 W/SA/K 12/5K	Cable/Lug	84333	190000	5000	5000	90	95	Hor ± 15*	10.50	1	MH
MS 1000 W/BU/BT37/PS/740	E39	71722	115000	12000	4000	68	115	Base Up ± 15*	4.20	6	MH
MH 1000 W/U/BT37/740	E39	15332	110000	12000	4000	65	110	Universal	4.20	6	MH
MS 1000 W/HOR/SPORT 60	EP39	47503	115000	12000	3400	70	115	Hor ± 60*	4.20	6	MH
MS 1500 W/HOR/XP/SPORT60	E39	82070	162000	3000	3400	70	108	Hor ± 60*	6.70	6	MH
MH 1500 W/U/XL	E39	12342	170000	4500	4000	65	113	Universal	6.70	6	MH
MH 2000 W/U/BT56/740	E39	36594	165000	3000	4000	65	83	Universal	10.30	6	MH