


T5 INTEGRATED LED TUBE BATTEN

Linero



Product ID *	A	B	C
VL/ITL-T5-LED0106x	580	36	22
VL/ITL-T5-LED0186x	1185	36	22
VL/ITL-T5-LED0206x	1185	36	22
VL/ITL-T5-LED0246x	1185	36	22

All Dimensions in "mm"

Specifications & Features

- * Extruded Aluminum housing with highly efficient PC Opal Diffuser
- * High energy saving Vis a Vis Traditional fluorescent - 50% compared to T8 and 35% compared to T5 FTL fixture
- * Direct power supply port with feasibility for series connection
- * Over load, over voltage, short circuit and reverse polarity protection
- * Integrated constant current driver with PF > 95%
- * More than 85% driver efficiency with < 20% Current THD
- * Equipped with 2.5KV Surge Protection
- * Wide operating voltage 120 - 290Vac
- * Color Rendering Index (CRI) > 80
- * Working ambient temperature -20°C to +45°C
- * Rated Life 50,000 Hrs (Ta = 30°C @ L70)
- * High intensity of illumination with 120° beam angle
- * Uniform diffuse & excellent glare control
- * Instant start without flash & humming
- * Electric wave & radio interference free
- * Without mercury, UV & IR radiation
- * IP 20 Ingress Protection

Applications

- * Office
- * Institutions
- * Hospitality
- * Residential lighting
- * Departmental stores
- * Factories

Installation & Maintenance

- * Mounted with wall mounting bracket
- * Power Supply should be disconnected before service

Note: Earthing (⊕) must be connected properly to avoid any premature failure.



Technical & Ordering Information

Product ID / Ordering Code	Product Description	Wattage(W)	Nominal Voltage(V)	Mains Current(A)	CCT (K)	Lumen (lm)
VL/ITL-T5-LED01065	Linero Intergated T5 LED batten 10/CW L600	10	230	0.045	5700 - 6500	1000
VL/ITL-T5-LED01865	Linero Intergated T5 LED batten 18/CW L600	18	230	0.082	5700 - 6500	1800
VL/ITL-T5-LED02065	Linero Intergated T5 LED batten 20/CW L1200	20	230	0.090	5700 - 6500	2000
VL/ITL-T5-LED02465	Linero Intergated T5 LED batten 24/CW L1200	24	230	0.110	5700 - 6500	2400

Intensity Distribution Diagram

