


Linear Trunk Light



Product ID *	L	W	H
VL/ITL-417-40xx	1520	750	750
VL/ITL-417-60xx	1520	750	750
VL/ITL-417-80xx	3040	750	750

All dimensions are in "mm"



Specifications & Features

- * High pressure performance LED mounted to an heat sink
- * Proper thermal management system
- * Highly efficient optical grade polymer acrylic lenses
- * 60% energy saving Vis a Vis Conventional HID linear light
- * Overload, over voltage & short circuit protection
- * Isolated constant current driver with PF > 90%
- * More than 90% driver efficiency with THDi < 10%
- * Equipped with 5KV Surge suppression protection
- * Wide operating voltage 120 - 280V
- * Color Rendering Index (CRI) > 80
- * Working ambient temperature -20°C to +40°C
- * Rated life 50,000 Hrs (Ta = 30°C @ L70)
- * High intensity of illumination with 120° view angle
- * Secondary lens and reflector provide desired light distribution
- * Flicker free instant reference free

Applications

- * Factory
- * Warehouse
- * Industrial areas
- * Super market
- * Offices
- * Cold storage

Installation & Maintenance

- * Mounting with hook, chain or cable
- * Power supply should be disconnected before service

COMPLIANCE



Note: Earthing (⊕) must be connected properly to avoid any premature failure.

Technical & ordering information

Product ID / Ordering Code	Product Description	Wattage (W)	Nominal Voltage (V)	Mains Current (A)	CCT (K)	Lumen (lm)
VL/ITL-417-04057	LED Linear Trunk 40/CW L1200	40	230	0.12	5700	4500
VL/ITL-417-06057	LED Linear Trunk 60/CW L1200	60	230	0.15	5700	6500
VL/ITL-417-08057	LED Linear Trunk 80/CW L1200	80	230	0.24	5700	8800

*xx also available in 4000K & 6000K CCTs on request

*xx also available with lens & without lens

Intensity Distribution Diagram

Light Intensity curve for reference only

