


I-Line



Product ID *	A	B	C
VL/ITL-300-LED0010xx	600	34	32
VL/ITL-300-LED0018xx	1200	34	32
VL/ITL-300-LED0020xx	1200	34	32
VL/ITL-300-LED0024xx	1200	34	32

All Dimension in "mm"



Specifications & Features

- * Extruded Aluminum batten with highly efficient PC Opal Diffuser
- * High energy saving Vis a Vis Traditional fluorescent tube- 50 % compared to T8 or, T12 FTL and 35% to T5 FTL
- * Direct power supply port with feasibility for series connection
- * Over load, over voltage, short circuit and reverse polarity protection
- * Integrated constant current driver with PF > 95%
- * More than 85% driver efficiency with < 20% current
- * Equipped with 2.5KV Surge protection
- * Wide operating voltage 100 - 277Vac
- * Color Rendering Index (CRI) > 80
- * Working ambient temperature -20°C to +45°C
- * Rated life 50,000 Hrs (Ta = 30°C @ L70)
- * High intensity of illumination with 120° beam angle
- * Uniform diffuse & excellent glare control
- * Instant start without flash & humming
- * Electric wave & radio interference free
- * Without mercury, UV & IR radiation
- * IP 20 Ingress protection

Applications

- * Office
- * Institutions
- * Hospitality
- * Residential lighting
- * Departmental stores
- * High Ceiling lighting
- * Factories

Installation & Maintenance

- * Mounted with wall mounting bracket
- * Power supply should be disconnected before service

Note: Earthing (⊕) must be connected properly to avoid any premature failure.



Technical & Ordering Information

Product ID / Ordering code	Product Description	Wattage (W)	Nominal Voltage (V)	Mains Current (A)	CCT (K)	Lumen (lm)
VL/ITL-300-LED001065	I-Line Integrated T8 LED batten 10/CW L600	10	230	0.045	6500	900
VL/ITL-300-LED001865	I-Line Integrated T8 LED batten 18/CW L1200	18	230	0.082	6500	1650
VL/ITL-300-LED002065	I-Line Integrated T8 LED batten 20/CW L1200	20	230	0.090	6500	1800
VL/ITL-300-LED002465	I-Line Integrated T8 LED batten 24/CW L1200	24	230	0.110	6500	2160

Intensity Distribution Diagram

